


FEATURES

- Tailor made product for perfect fit with your CIPP
- Well proven pipe locking system (developed continuously since 1997)
- Multi-material end restraint system
- Separate sealing and end restraint
- Resistant to corrosion
- Only one restraint connection needed (compared to competitor systems)
- Different connection systems available (rotatable flange, fixed flange, spigot ends, etc.)
- All inner- and outer-diameters from DN 300 – DN 1500 available
- Special solutions for inner- and outer- diameters from DN 300 to DN 1200 available - other dimensions on request
- Fast and easy installation

MATERIALS

- Body and compression flange: S235JR steel
- Bolts, nuts, washers: zinc coated steel Alternative: grade A2 AISI 304 SS
- Sealing rings: EPDM or NBR on request
- End restraint grippers: tempered steel with Dacromet coating
Alternative: martensitic stainless steel grippers
- Anticorrosion coating RILSAN NYLON 11

MEDIUM



Water

Sewage



PIPE MATERIALS

Restraint

- Steel
- Cast Iron

Non restraint

(Connection for anchoring in the trench available)

- Cement
- Asbestos cement

ADVANTAGES

- Fits perfect in combination with the CIPP
- Customized ID
- Easy work during the planning
- All parts fit together:
CIPJOINT – GRP liner – end seals

